



Piano Basic – Plus – Plus VRA

CLINICAL AUDIOMETER

DESCRIPTION

Piano is an advanced clinical audiometer with two separate and independent channels. Piano features a complete battery of tests, all easily managed via a wide touch screen color display.

The “Plus VRA” version of the Piano audiometer forms the heart of a professional VRA system and can use as reinforces either traditional cabinet toys or videos and images on one or more displays.

CLASSIFICATION

- EN 60645-1 / ANSI S3.6: Type 1
- EN 60645-2 / ANSI S3.6: Type A or A-E
- EN 60645-4 / ANSI S3.6: Compliant (Piano Plus / Plus VRA only)

AVAILABLE SIGNALS

- Stimulus: pure tone, warble tone
- 2 external inputs for speech audiometry
- MIC input for live speech audiometry
- Internal input (flash memory) for speech audiometry
- Masking: NBN, WN, SN

SIGNALS SPECIFICATION

- Attenuator step: 1 and 5 dB
- Presentation: Continuous, Pulsed (0.5, 1 and 2 Hz or custom freq.), Single Pulse (with selectable duration)
- Warble: 5 Hz sin wave modulating signal

AVAILABLE OUTPUTS AND TRANSDUCERS

- AC: TDH-39 or DD45 headphones, ER-3 / ER-5 insert earphones, HDA-200 or HDA-300 headphones (Piano Plus / Plus VRA only)
- BC: B-71 bone vibrator
- Free field
- Insert masking earphone: IME-100

AVAILABLE TESTS

- Pure Tone audiometry
- Auto threshold (modified Hughson-Westlake)
- Speech audiometry (2 channels)
- ABLB
- MLB
- SISI: automatic score; 1 dB increment (5 dB for familiarization)
- DLI, with increments between 0 and 5 dB
- Tone decay, with 60 or 120 sec. duration
- Stenger, with pure tone or speech stimulation
- 2 independent channels Master Hearing Aid
- TEN test
- QuickSIN® test (optional)

Only on Piano Plus:

- HF audiometry: from 8 to 20 kHz
- Multi Frequency: frequency steps selectable between 1/3, 1/6, 1/12 and 1/24 octave
- Bekesy Test: 125 Hz to 8 kHz fixed or sweep frequency, continuous or pulsed tone
- Masking Level Difference (MLD): noise and / or signal out of phase

Only on Piano Plus VRA:

- Visual Reinforcement Audiometry (VRA) test
- Conditioned Play Audiometry (CPA) test

PURE TONE: FREQUENCIES AND MAXIMUM LEVELS (dB HL)

Freq. (Hz)	AC TDH-39 DD45	AC HDA-200 HDA-300	AC ER-3	AC ER-5	BC	FF (*)
125	80	85	90	90	-	75
250	100	100	105	100	45	85
500	120	110	110	110	65	95
750	120	110	115	120	70	95
1.000	120	110	120	120	75	95
1.500	120	110	120	120	80	95
2.000	120	110	120	115	80	95
3.000	120	110	120	115	75	95
4.000	120	105	110	110	75	95
6.000	110	100	100	100	55	90
8.000	100	90	90	90	50	85
9.000	-	90	-	-	-	80
10.000	-	90	-	-	-	80
11.200	-	90	-	-	-	80
12.500	-	80	-	-	-	80
14.000	-	70	-	-	-	80
16.000	-	50	-	-	-	50
18.000	-	110 dB SPL	-	-	-	-
20.000	-	110 dB SPL	-	-	-	-

(*) The values refer to “normal” range; add 10 dB to each value in case of “extended range” option selected

SPEECH AUDIOMETRY: MAXIMUM LEVELS (dB HL)

AC TDH-39 DD45	AC HDA-200 HDA-300	AC ER-3	AC ER-5	BC	FF
100	90	100	100	55	Normal: 75 Extended: 85

PATIENT – OPERATOR COMMUNICATION

Talk over: built-in or external microphone
 Talk back: through built-in speaker or monitor headset (included); clip-on patient microphone included
 Up to 2 patient response buttons (left and right)

MONITOR SIGNAL

Both channels and patient voice monitored through the built-in speaker or monitor headset (included)

PRINTER

Optional integrated thermal printer. Paper size: 112 mm

INTERNAL FLASH MEMORY

Used to store the speech material (.wav format)
Capacity: 2 GB (more than 3 hours of speech)
Speech material upload: through ATIT software (incl.)

CALIBRATION

Validity: 12 months.
All the parameters set through the device software

COMPUTER INTERFACE

Connection: USB (driverless)
Compatible software: - Inventis Daisy with Maestro module
- Noah with "Maestro for Noah" module

HYBRID TECHNOLOGY

Description: Piano can be controlled either as a stand-alone or as a PC-controlled audiometer
It requires Daisy or Noah Maestro module

DISPLAY

Type: Graphical colour TFT LCD. Size: diagonal 7", 150 mm x 90 mm
Resolution: 800 x 480. Resistive touch screen

POWER SUPPLY

Without integrated printer:
Maximum consumption: 9 Watts
Power supply: 6V, 2A cont., through an external medical grade 100-240 Vac 50/60 Hz power supply

With integrated printer:
Maximum consumption: 25 Watts
Power supply: 6V, 4,16A cont., through an external medical grade 100-240 Vac 50/60 Hz power supply

MECHANICS

Without integrated printer:
Size (WxDxH): 32 x 32 x 15 cm / 12.6 x 12.6 x 5.9 in
Weight: 2 Kg / 4.4 lbs

With integrated printer:
Size (WxDxH): 32 x 39 x 15 cm / 12.6 x 15.4 x 5.9 in
Weight: 2.5 Kg / 5.5 lbs

FREIGHT PACKING

Size (WxDxH): 47 x 40 x 35 cm / 18.5 x 15.8 x 13.8 in
Gross weight (without printer): 4.4 Kg / 9.7 lbs
Gross weight (with printer): 4.9 Kg / 10.8 lbs

APPLICABLE STANDARDS

Pure tone audiometry: EN 60645-1, Type 1
Speech audiometry: EN 60645-2, Type A or A-E (depending on the equalization filter status)
High Frequency audiometry: EN 60645-4
Calibration: EN ISO 389-1 (TDH 39), EN ISO 389-2 (ER-3 and ER-5), EN ISO 389-3 (B71), EN ISO 389-5 (HF), EN ISO 389-7 (FF), data from the manufacturer (DD45 and HDA-300 headphones)
Electrical safety: EN 60601-1, Class I type BF
EMC: EN 60601-1-2

Piano is developed by Inventis s.r.l.
info@inventis.it
www.inventis.it



The Inventis Quality System complies with ISO 9001 and ISO 13485 standards.

CE CERTIFICATE

93/42/EEC classification : Class IIa
Classification rule (Annex IX, 93/42/EEC): 10
Notified body: TÜV SÜD Product Service GmbH (0123)
Number of CE certificate: G1 12 09 65346 006

PRODUCT CODES

10147: Piano model Basic – Clinical audiometer
10164: Piano model Basic – Clinical audiometer – with integrated thermal printer
10148: Piano model Plus – Clinical audiometer
10165: Piano model Plus – Clinical audiometer – with integrated thermal printer
10300: Piano model Plus VRA – Clinical audiometer with VRA exam
10306: Piano model Plus VRA – Clinical audiometer with VRA exam – with integrated thermal printer

INCLUDED PARTS

- TDH-39 or DD45 supra-aural headphones
- HDA-200 or HDA-300 headphones (Piano Plus / Plus VRA only)
- B71 bone vibrator
- Patient response switch
- Monitor headset with boom microphone
- Clip-on microphone for patient-to-operator communication
- Plastic cover sheet
- Medical grade power supply
- USB connection cable
- User manual
- Inventis Software Suite CD
- Desktop response switch for children (Piano Plus VRA only)

OPTIONAL ACCESSORIES (with order code)

- 10166: ER-3A insert earphones
- 10833: ER-3C insert earphones
- 10172: ER-5A insert earphones
- 10177: IME-100 insert masking earphone
- 10181: Desktop, battery operated microphone for live speech tests
- 10179: Amplivox Audiocups noise excluding enclosures for TDH-39 / DD45 headphones
- 10257: Additional patient response switch
- 10180: Cable set for sound booth
- 10182: Soft carrying case
- 10541: Trolley for audiometers / tympanometers
- 10293: Thermal paper for Harp and Piano audiometers (box of 5)
- 10266: One active speaker FBT J-5A
- 10533: QuickSIN® test license

Only for Piano Plus VRA:

- 10301: Visual Reinforcement for Piano VRA – Kit The Bunny
- 10302: Visual Reinforcement for Piano VRA – Peanuts the Dog
- 10303: Visual Reinforcement for Piano VRA – Jack the Donkey
- 10053: Dedicated table for Pediatric Audiometry systems
- 10307: Stand for toy and speaker
- 10308: Pre-configured mini-tower computer with 4 video outputs - includes the webcam