



Clarinet Basic - Plus

CLINICAL MIDDLE EAR ANALYZER



CLASSIFICATION

EN 60645-5 / ANSI S3.39: Type 1

PROBE TONES

Frequency: 226 Hz
 678, 800, 1000 Hz (Clarinet Plus only)
 Level: 85 dB SPL (@ 226 Hz)
 80 dB SPL (@ 678 Hz)
 75 dB SPL (@ 800, 1000 Hz)

ADMITTANCE MEASUREMENT SYSTEM

Measurement range: -2 ÷ 8.0 mmho (@ 226 Hz)
 -4 ÷ 16.0 mmho (@ 678, 800 and 1000 Hz)

PRESSURE SYSTEM

Rotary type pump with endless flow

AVAILABLE TESTS

- Tympanometry (automatic and manual)
- Multi-component tympanometry (Plus only)
- Acoustic Reflex Threshold (automatic and manual)
- Acoustic Reflex Decay
- Acoustic Reflex Latency
- Eustachian Tube Function (intact and perforated TM)

TYMPANOMETRY

Viewing mode: absolute or compensated
 Measured components: Admittance [Y]
 Susceptance [B] (Clarinet Plus only)
 Conductance [G] (Clarinet Plus only)
 Single or multiple scan (up to 3)
 Selectable sweep direction
 User selectable pressure range
 Maximum range: -600 to +400 daPa
 Safety limits: -800 daPa and +600 daPa
 Available rates: 15, 50, 100, 200, 300, 400, 600 daPa/sec and AUTO
 (200-600 daPa/sec)
 Manual pressure adjustment
 Auto start feature

ACOUSTIC REFLEX TEST

Ipsilateral and contralateral stimulation
 Non-acoustic stimulation
 Stimulus ON-Time: selectable from 0.5s to 2.5s
 Stimulus OFF-Time: selectable from 0.5s to 2.5s
 Four different tests available:

- Automatic threshold
- Fixed intensity
- Growing intensity
- Manual mode

ACOUSTIC REFLEX DECAY TEST

Ipsilateral and contralateral stimulation
 Non-acoustic stimulation
 Test duration: 10 sec or 20 sec (selectable)

ACOUSTIC REFLEX LATENCY TEST

Ipsilateral and contralateral stimulation
 Stimulus ON-Time: selectable from 0.3s to 1.7s
 Stimulus OFF-Time: selectable from 0.3s to 1.7s
 ON-Angle and OFF-Angle measurement: incidence angle of the acoustic reflex slopes

EUSTACHIAN TUBE FUNCTION TEST

ETF with TM intact: Williams test
 ETF with perforated TM: Toynbee test, with customizable duration and pressure range

QUICK TESTS

Two user programmable Quick tests available
 Each test consists of a sequence of

- Tympanometry
- Reflex test (Fixed intensity or Automatic threshold, with user defined parameters)

AVAILABLE STIMULI AND MAXIMUM LEVELS

Attenuator step: 1, 2 and 5 dB

Stimulus	IPSI (dB HL)	CONTRA TDH39 headphone (dB HL)	CONTRA IME-100 earphone (dB HL)
250 Hz	-	100	100
500 Hz	100	120	110
1,000 Hz	110	120	115
2,000 Hz	105	120	110
3,000 Hz	105	120	110
4,000 Hz	100	120	110
6,000 Hz	100	105	100
8,000 Hz	-	100	-
BBN	95	115	105
LPN	95	115	105
HPN	95	115	105

PRINTER

Optional integrated thermal printer
 Paper size: 112 mm

CALIBRATION

Validity: 12 months
 All the parameters set through the device software

COMPUTER INTERFACE

Connection: USB (driverless)
 Compatible software: Inventis Daisy with Maestro module, Noah with Noah Maestro module

DISPLAY

Type: Graphical color TFT LCD
 Size: diagonal 7", 150 mm x 90 mm
 Resolution: 800 x 480
 Resistive touch screen

POWER SUPPLY

Without integrated printer:

Maximum consumption: 8 Watts
 Power supply: 6V, 2A cont., through an external medical grade 100-240 Vac 50/60 Hz

With integrated printer:

Maximum consumption: 25 Watts
 Power supply: 6V, 4,16A cont., through an external medical grade 100-240 Vac 50/60 Hz

MECHANICS

Without integrated printer:

Size (WxDxH): 32 x 32 x 15 cm / 12.6 x 12.6 x 5.9 in
 Weight: 2.0 Kg / 4.4lbs

With integrated printer:

Size (WxDxH): 32 x 39 x 15 cm / 12.6 x 15.4 x 5.9 in
 Weight: 2.5 Kg / 5.5lbs

FREIGHT PACKING

Size (WxDxH): 47 x 42 x 35 cm / 18.5 x 15.8 x 13.8 in
 Gross weight (without printer): 4.4 Kg / 9.7lbs
 Gross weight (with printer): 4.9 Kg / 10.8lbs

APPLICABLE STANDARDS

Impedance: EN 60645-5 / ANSI S3.39, Type 1
 Electrical safety: EN 60601-1
 EMC: EN 60601-1-2

CE CERTIFICATE

93/42/EEC classification: Class IIa
 Classification rule (Annex IX, 93/42/EEC): 10
 Notified body: TÜV SÜD Product Service GmbH [0123]
 Number of CE certificate: G1 12 09 65346 006

PRODUCT CODES

10517: Clarinet model Basic
 10518: Clarinet model Basic – With integrated thermal printer
 10542: Clarinet model Plus
 10543: Clarinet model Plus – With integrated thermal printer

INCLUDED PARTS

- Control unit with probe
- Shoulder strap for probe control box
- Wrist strap for probe control box
- Single TDH-39 contralateral headset
- Calibration cavities
- Assorted ear tips box
- Plastic cover sheet

- Medical grade power supply
- USB connection cable
- User manual
- Inventis Software Suite CD
- Noah Maestro module

OPTIONAL ACCESSORIES (with order code)

- 10149: Daisy Maestro module
- 10342: Insert earphone for contra reflex testing
- 10293: Thermal paper for printer (box of 5)
- 10182: Soft carrying case
- 10541: Trolley for audiometers / tympanometers

DISPOSABLES (with order code)

- 10488: White tips (diam. 6 mm) – Set of 30
- 10489: Pink tips (diam. 7 mm) – Set of 30
- 10490: Violet tips (diam. 8 mm) – Set of 30
- 10491: Green tips (diam. 10 mm) – Set of 30
- 10492: Red tips (diam. 12 mm) – Set of 30
- 10493: Blue tips (diam. 14 mm) – Set of 30
- 10494: Orange tips (diam. 16 mm) – Set of 30
- 10495: Light blue tips (diam. 18 mm) – Set of 30
- 10496: Yellow tips (diam. 21 mm) – Set of 30
- 10511: Box with assorted tips – Set of 160
- 10554: Cleaning brushes for the tympanometers probe

Clarinet is developed by:

INVENTIS s.r.l.

CORSO STATI UNITI, 1/3
 35127 PADOVA – ITALY
 PHONE: +39.049.8962 844
 FAX: +39.049.8966 343
 info@inventis.it
 www.inventis.it

Follow us on Twitter
<http://twitter.com/inventissrl>



The Inventis Quality System complies with ISO 9001 and ISO 13485 standards.

Inventis® is a registered trademark of Inventis s.r.l.