

signia

Life sounds brilliant.

Silk™ X 7/5/3/2/1

Ready-to-wear hearing instrument

All data specified were determined under test conditions which comply with the Specifications of Hearing Aid Characteristics ANSI S3.22-2014.

Hearing aid test settings according to the test mode, selectable from the Connexx® fitting menu, configures the instrument for full-on gain, no compression and all adaptive signal analysis and processing turned off.

- Battery life stated is measured at 65 dB input and reference test gain.
- Actual battery life depends on the output level.


Standard ANSI S3.22-2014

2 ccm coupler

Output	Peak OSPL 90	114 dB
	HF - average OSPL 90	108 dB
Full-on gain	Peak	50 dB
	HF - average	45 dB
	Reference test gain	31 dB
Frequency range	Low frequency limit	100 Hz
	High frequency limit 7X	8600 Hz
	High frequency limit 5X/3X	8000 Hz
Total harmonic distortion	500 Hz	2%
	800 Hz	3%
	1600 Hz	2%
	3200 Hz	1%
Equivalent input noise		20 dB
Battery current drain		1.3 mA
Battery life (typical) #10 zinc air battery		~70 h



Output Sound Pressure Level
2 ccm coupler,
ANSI S3.22-2014



Frequency Response
2 ccm coupler,
ANSI S3.22-2014

